


- √ Smart & Elegant
- ✓ Easy to Maintain
- ✓ Prevents Slipping
 & Falling
- ✓ Protects the Interior Floor Furnishes







"A high quality product made from a combination of aluminium alloy extrusion, hard-wearing resilient carpet and durable vinyl"

4 Choices of Framework

Four Choices of Framework to suit your requirements:



DS PLATINUM MAT

- Versatile for modern construction applications
- Suitable for heavy human traffic
- Accessible for wheeled traffic
- Heel Proof

Thickness: 10mm

Recess Depth: 14mm

Weight: 12.50 kg/m²





DS FLEXI MAT

- Able to roll up for easy cleaning
- Good water drainage system
- Suitable for heavy human traffic
- Accessible for wheeled traffic
- Heel Proof

Thickness: 16mm

Recess Depth: 20mm

Weight: 14.10 kg/m²





DS ULTRA-FLEXI MAT

- A modified version of DS Flexi Mat
- Greater carpet exposure
- Optimal water absorption
- Excellent acoustic performance

Thickness: 16mm

Recess Depth : 20mm

Weight: 13.40 kg/m²






DS DELUXE MAT

- The latest design of DS Series
- Slim line yet stunning in performance
- Able to roll up for easy cleaning
- Excellent acoustic performance

Thickness: 16mm

Recess Depth : 20mm

Weight: 14.30 kg/m²



"Innovative design, integrating with quality and functional details, enhance it's durability to function at optimum capacity"

Range of Colours

Choices of Inserts to suit your requirements:




DS Platinum Mat

DS Platinum Mat is the perfect solution for mass market application. They are commonly used in supermarkets, hotels, schools, private residential buildings, banks, government offices, markets, toilet entrances, where dirt trapping is the first priority.

There is a wide range of colours to choose to match the surrounding floor finishes. Carpets inserts or Vinyl inserts can be specified individually or in combination to be fitted into the aluminium treads. The rigid structure ensures complete silence while in use. Among all, this mat has the most un-complex structure which makes it most economical and popular.



- Versatile for modern construction applications
- Suitable for heavy human traffic
- Accessible for wheeled traffic
- Heel Proof



Model	DS Platinum Mat
Thickness	10mm
Carpet Threads	100% Polypropylene with
	Acrylic Resin Lock Coat
Carpet Texture	Velour
Flammability	Tested to AS 1503.3
L AngleFrame	12mm x 25mm x 3mm
	thick made of aluminium
	extrusion grade 6063-T6
Filler Block	Up to 10mm thick made
	of aluminium extrusion
	grade 6063-T6
Aluminium Rail	50mm wide made of
	aluminium extension
	grade 6063-T6
Base Cushion	Polyvinyl Chloride (Black)
	Shore A (60 deg +/- 5)







Bronze

Black


Insert Options





Carpet

Vinyl



DS Flexi Mat

DS Flexi Mat is the perfect choice for outdoors application. It features capacity to collect large amount of dirt and water.


Between the aluminium rails, the joint is made of high resilient vinyl with perforated holes.

During downpour, the rain water will flow through the holes and discharge through the floor traps found beneath the mats, thus prevents the mats from excessive soaking.

DS Flexi Mat provides effective solution for dirt and water control even before it has chance to enter the building.



- Able to roll up for easy cleaning
- Good water drainage system
- Suitable for heavy human traffic
- Accessible for wheeled traffic
- Heel Proof



Model	DS FLEXI MAT
Thickness	16mm
Carpet Threads	100% Polypropylene with Acrylic Resin Lock Coat
Carpet Texture	Velour
Flammability	Tested to AS 1503.3
L Angle Frame	20mm x 20mm x 3mm thick made of aluminium extrusion grade 6063-T6
Filler Block	Up to 16mm thick made of aluminium extrusion grade 6063-T6
Aluminium Rail	38mm wide made of aluminium extension grade 6063-T6
Base Cushion	Foam Strip





Bronze




Insert Options





Specifications





DS Ultra-Flexi Mat

This is a modified version of the DS Flexi Mat.

The carpet appears more prominent thus giving a sleek and softer touch.

DS Ultra-Flexi Mat offers comfort without compromise of elegant touch to the surrounding. It has an excellent drainage system when water absorption is critical. It can be conveniently rolled up for easy cleaning and storage.









- A modified version of DS Flexi Mat
- Greater carpet exposure
- Optimal water absorption
- Excellent acoustic performance




Model	DS Ultra-Flexi Mat
Thickness	16mm
Carpet Threads	100% Polypropylene with Acrylic Resin Lock Coat
Carpet Texture	Velour
Flammability	Tested to AS 1503.3
L Angle Frame	20mm x 20mm x 3mm thick made of aluminium extrusion grade 6063-T6
Filler Block	Up to 16mm thick made of aluminium extrusion grade 6063-T6
Aluminium Rail	38mm wide made of aluminium extension grade 6063-T6
Base Cushion	Foam Strip



Insert Options







DS Deluxe Mat

DS Deluxe Mat is our latest design. The aluminium rails boost a streamline design which gives a sleek and stylish framework. It is made of high performance sturdy structure, suitable for high volume traffic area such as shopping malls, train stations, airport terminals, market places, conventional halls, libraries and food courts.

The ultimate design offers excellent dirt control capabilities.










- The latest design of DS Series
- Slim line yet stunning in performance
- Able to roll up for easy cleaning
- Excellent acoustic performance



Model	DS Deluxe Mat
Thickness	16mm
Carpet Threads	100% Polypropylene with Acrylic Resin Lock Coat
Carpet Texture	Velour
Flammability	Tested to AS 1503.3
L Angle Frame	20mm x 20mm x 3mm thick made of aluminium extrusion grade 6063-T6
Filler Block	Up to 16mm thick made of aluminium extrusion grade 6063-T6
Aluminium Rail	28mm wide made of aluminium extension grade 6063-T6
Base Cushion	Foam Strip










Black

Specifications



Mats Performance

Dorsmat entrance floor mat undergoes the following stringent tests to ensure they satisfy the requirements before putting into use.

If you need further technical advice and support, please call us at:

(65) 6966-7680





- Flammability Test in accordance with
 AS 1502.3
- Rolling Load test up to 1500kg
- Slip resistance in accordance with ASTM C1028-07
- Static Coefficient of friction (Dry), 0.75
- Static Coefficient of friction (Wet), 0.70







"Innovative design, integrating with quality and functional details"



Tampinesmall If you have any further enquiries, please e-mail us at: sales@darmour.sq Condominium Tampines Shopping Mall

Cleaning Instructions

Regular Maintenance will prolong the life span of the entrance floor mat. Take note on the following points.

- The mat has to be vacuumed regularly. Avoid washing or scrubbing the mat with water and detergent.
- For spot stains, localised shampooing, steam cleaning and dry with a soft air blower.
- Once a week, wax the vinyl treats with silicon based solvent will help to keep the lustre look of the vinyl.
- The aluminium treads should be gently wiped with clean water. Avoid using strong solvent, acid, abrasive solution or dirty water to clean the threads.
- Use of hard brooms, scrapers or wired brushes are strongly discouraged.
- High powered air blowers and pressure cleaners should only be used with proper supervision.
- DS Platinum Mats should not be regularly lifted for cleaning. This may damage the framework due to mishandling.
- Worn carpets should be replaced immediately. Please contact your nearest distributor outlet.



DS PLATINUM MAT













Important Notes

All the information supplied in this brochure is to our best knowledge. They should be used as a guide and not as a guarantee.

Technical specifications in this brochure are subjected to changes without prior

notice.

the owner.



Your Local Representative